



# Safety Data Sheet

## Spartan Chemical Company, Inc.

Revision Date: 10-Apr-2020

### 1. PRODUCT AND COMPANY IDENTIFICATION

#### Product Identifier

**Product Name:** XTREME BUG BLASTER PRE-SPRAY  
**Product Number:** 2666  
**Recommended Use:** Cleaning agent  
**Uses Advised Against:** For Industrial and Institutional Use Only

**Manufacturer/Supplier:** Spartan Chemical Company, Inc.  
1110 Spartan Drive  
Maumee, Ohio 43537 USA  
800-537-8990 (Business hours)  
[www.spartanchemical.com](http://www.spartanchemical.com)

#### **24 Hour Emergency Phone Numbers:**

**Medical Emergency/Information:** 888-314-6171  
**Transportation/Spill/Leak:** CHEMTREC 800-424-9300

### 2. HAZARDS IDENTIFICATION

#### **GHS Classification**

**Skin Corrosion/Irritation:** Category 1 Sub-category B  
**Serious Eye Damage/Eye Irritation:** Category 1  
**Corrosive to Metals:** Category 1

#### **GHS Label Elements**

**Signal Word:**

**Danger**

**Symbols:**



**Hazard Statements:**

Causes severe skin burns and serious eye damage.  
May be corrosive to metals.

#### **Precautionary Statements:**

**Prevention:**

Do not breathe mist, vapors or spray.  
Wash hands and any exposed skin thoroughly after handling.  
Wear protective gloves. Wear eye / face protection. Wear protective clothing.  
Keep in original or other corrosion resistant container.

**Response:**

**-Eyes**

**IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN.**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

**-Skin**

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. Wash contaminated clothing before reuse.

**-Inhalation:**

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

**-Ingestion:**

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

**-Specific Treatment:**

See Safety Data Sheet Section 4: "FIRST AID MEASURES" for additional information.

**Spill:**

Absorb spillage to prevent material damage.

<b>Storage:</b>	Store locked up. Store in corrosion resistant container.
<b>Disposal:</b>	Dispose of contents and container in accordance with local, state and federal regulations.
<b>Hazards Not Otherwise Classified:</b>	Not Applicable
<b>Other Information:</b>	<ul style="list-style-type: none"> <li>• Corrosive.</li> <li>• Harmful if swallowed</li> <li>• Harmful contact may not cause immediate pain.</li> <li>• Inhalation of vapors or mist may cause respiratory irritation or damage.</li> <li>• Take off and destroy contaminated shoes.</li> <li>• Keep out of reach of children.</li> <li>• NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage.</li> </ul>

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Water	7732-18-5	60-100
Potassium Hydroxide	1310-58-3	1-5
PEG-15 Cocomonium Chloride	61791-10-4	1-5
Butoxyethanol	111-76-2	1-5
Sodium Laureth Sulfate	9004-82-4	1-5
C9-11 Pareth-6	68439-46-3	1-5
Tetrasodium EDTA	64-02-8	0.1-1
Lauramine Oxide	1643-20-5	0.1-1
CI 45350	6417-85-2	<0.1

Specific chemical identity and/or exact percentage of composition has been withheld as a trade secret.

### 4. FIRST AID MEASURES

<b>-Eye Contact:</b>	Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN.
<b>-Skin Contact:</b>	Take off immediately all contaminated clothing and shoes. Rinse with water or shower for at least 15 minutes. IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN. Wash contaminated clothing before reuse. Discard or destroy contaminated shoes.
<b>-Inhalation:</b>	Remove victim to fresh air and keep at rest in a position comfortable for breathing. IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN.
<b>-Ingestion:</b>	Rinse mouth. Do NOT induce vomiting. IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN. Never give anything by mouth to an unconscious person.
<b>Note to Physicians:</b>	NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage.

### 5. FIRE-FIGHTING MEASURES

<b>Suitable Extinguishing Media:</b>	Product does not support combustion, Use extinguishing agent suitable for type of surrounding fire
<b>Specific Hazards Arising from the Chemical:</b>	Dried product is capable of burning. Combustion products are toxic.
<b>Hazardous Combustion Products:</b>	May include Carbon monoxide Carbon dioxide and other toxic gases or vapors.
<b>Protective Equipment and Precautions for Firefighters:</b>	Wear MSHA/NIOSH approved self-contained breathing apparatus (SCBA) and full protective gear. Cool fire-exposed containers with water spray.

### 6. ACCIDENTAL RELEASE MEASURES

<b>Personal Precautions:</b>	Avoid contact with skin, eyes or clothing. Use personal protective equipment as required.
------------------------------	---

**Environmental Precautions:** Do not rinse spill onto the ground, into storm sewers or bodies of water.  
**Methods for Clean-Up:** Prevent further leakage or spillage if safe to do so. Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see Section 13).

## 7. HANDLING AND STORAGE

**Advice on Safe Handling:** Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly after handling.  
**Storage Conditions:** Keep containers tightly closed in a dry, cool and well-ventilated place. Keep out of the reach of children. Keep from freezing.  
**Incompatible Materials:** Strong acids. Reactive metals such as aluminum, zinc and tin.  
**Suggested Shelf Life:** Minimum of 2 years from date of manufacture.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### Occupational Exposure Limits:

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH
Potassium Hydroxide 1310-58-3	Ceiling: 2 mg/m <sup>3</sup>	(vacated) Ceiling: 2 mg/m <sup>3</sup>	Ceiling: 2 mg/m <sup>3</sup>
Butoxyethanol 111-76-2	TWA: 20 ppm	TWA: 50 ppm TWA: 240 mg/m <sup>3</sup> (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m <sup>3</sup> (vacated) S* S*	IDLH: 700 ppm TWA: 5 ppm TWA: 24 mg/m <sup>3</sup>

**Engineering Controls:** Provide good general ventilation.  
If work practices generate dust, fumes, gas, vapors or mists which expose workers to chemicals above the occupational exposure limits, local exhaust ventilation or other engineering controls should be considered.  
Eye wash stations and shower facilities should be readily accessible in areas where the product is handled.

**Personal Protective Equipment**

**Eye/Face Protection:** Wear splash goggles. For severe use-conditions, wear a face shield over the goggles.  
**Skin and Body Protection:** Wear rubber or other chemical-resistant gloves. Use of impervious apron, boots and other protective equipment should be considered in order to prevent or minimize contact with this product.

**Respiratory Protection:** Not required with expected use.  
If occupational exposure limits are exceeded or respiratory irritation occurs, use of a NIOSH/MSHA approved respirator suitable for the use-conditions and chemicals in Section 3 should be considered.

**General Hygiene Considerations:** Wash hands and any exposed skin thoroughly after handling.  
See 29 CFR 1910.132-138 for further guidance.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance/Physical State:</b>	Liquid
<b>Color:</b>	Neon Yellow
<b>Odor:</b>	solvent
<b>pH:</b>	13.5-14.00
<b>Melting Point / Freezing Point:</b>	No information available.
<b>Boiling Point / Boiling Range:</b>	100 °C / 212 °F
<b>Flash Point:</b>	> 100 °C / > 212 °F ASTM D56
<b>Evaporation Rate:</b>	< 1.0 (Butyl acetate = 1)
<b>Flammability (solid, gas)</b>	No information available.
<b>Upper Flammability Limit:</b>	No information available.
<b>Lower Flammability Limit:</b>	No information available.
<b>Vapor Pressure:</b>	No information available.
<b>Vapor Density:</b>	No information available.
<b>Specific Gravity:</b>	1.042
<b>Solubility(ies):</b>	Soluble in water
<b>Partition Coefficient:</b>	No information available.
<b>Autoignition Temperature:</b>	No information available.
<b>Decomposition Temperature:</b>	No information available.
<b>Viscosity:</b>	No information available.

## 10. STABILITY AND REACTIVITY

<b>Reactivity:</b>	This material is considered to be non-reactive under normal conditions of use.
<b>Chemical Stability:</b>	Stable under normal conditions.
<b>Possibility of Hazardous Reactions:</b>	Contact with aluminum or other reactive metals may release hydrogen gas.
<b>Conditions to Avoid:</b>	Extremes of temperature and direct sunlight.
<b>Incompatible Materials:</b>	Strong acids. Reactive metals such as aluminum, zinc and tin.
<b>Hazardous Decomposition Products:</b>	May include carbon monoxide, carbon dioxide (CO <sub>2</sub> ) and other toxic gases or vapors.

## 11. TOXICOLOGICAL INFORMATION

<b>Likely Routes of Exposure:</b>	Eyes, Skin, Ingestion, Inhalation.
<b>Symptoms of Exposure:</b>	
<b>-Eye Contact:</b>	Pain, redness, swelling of the conjunctiva and tissue damage. Eye contact may cause permanent damage.
<b>-Skin Contact:</b>	Pain, redness, blistering and possible chemical burn.
<b>-Inhalation:</b>	Irritation or damage to the mucus membranes of the respiratory tract. Nasal discomfort and coughing.
<b>-Ingestion:</b>	Damage or chemical burns to mouth, throat and stomach. Pain, nausea, vomiting and diarrhea.
<b>Immediate, Delayed, Chronic Effects</b>	
Product Information:	Data not available or insufficient for classification.
Target Organ Effects:	Blood. Central nervous system. -Eyes. hematopoietic system. kidney. Liver. Respiratory System. -Skin.
<b>Numerical Measures of Toxicity</b>	
The following acute toxicity estimates (ATE) are calculated based on the GHS document.	
ATEmix (oral):	4020 mg/kg
ATEmix (dermal):	36593 mg/kg
ATEmix (inhalation-dust/mist):	49.9 mg/l
ATEmix (inhalation-vapor):	366 mg/l

### Component Acute Toxicity Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Water 7732-18-5	> 90 mL/kg ( Rat )	Not Available	Not Available

Potassium Hydroxide 1310-58-3	= 284 mg/kg ( Rat )	Not Available	Not Available
PEG-15 Cocomonium Chloride 61791-10-4	= 580 mg/kg ( Rat )	Not Available	Not Available
Butoxyethanol 111-76-2	= 470 mg/kg ( Rat )	= 99 mg/kg ( Rabbit )	= 450 ppm ( Rat ) 4 h
Sodium Laureth Sulfate 9004-82-4	= 1600 mg/kg ( Rat )	Not Available	Not Available
C9-11 Pareth-6 68439-46-3	= 1400 mg/kg ( Rat )	Not Available	Not Available
Tetrasodium EDTA 64-02-8	= 1658 mg/kg ( Rat )	Not Available	Not Available

**Carcinogenicity:** The table below indicates whether each agency has listed any ingredient as a carcinogen.

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

Chemical Name	Algae/Aquatic Plants	Fish	Toxicity to Microorganisms	Crustacea
Butoxyethanol 111-76-2	Not Available	1490: 96 h Lepomis macrochirus mg/L LC50 static 2950: 96 h Lepomis macrochirus mg/L LC50	Not Available	1000: 48 h Daphnia magna mg/L EC50
Tetrasodium EDTA 64-02-8	1.01: 72 h Desmodesmus subspicatus mg/L EC50	41: 96 h Lepomis macrochirus mg/L LC50 static 59.8: 96 h Pimephales promelas mg/L LC50 static	Not Available	Not Available

**Persistence and Degradability:** No information available.

**Bioaccumulation:** No information available.

**Other Adverse Effects:** No information available.

## 13. DISPOSAL CONSIDERATIONS

**Disposal of Wastes:** Dispose of in accordance with federal, state and local regulations.

**Contaminated Packaging:** Dispose of in accordance with federal, state and local regulations.

## 14. TRANSPORT INFORMATION

**DOT:**

**UN/ID No:** UN1760  
**Proper Shipping Name:** Corrosive liquids, n.o.s., (contains potassium hydroxide)  
**Hazard Class:** 8  
**Packing Group:** II  
**Special Provisions:** Shipping descriptions may vary based on mode of transport, quantities, package size, and/or origin and destination. Check with a trained hazardous materials transportation expert for information specific to your situation.

**UN/ID No:** UN1760  
**Proper Shipping Name:** Corrosive liquids, n.o.s., (contains potassium hydroxide)  
**Hazard Class:** 8  
**Packing Group:** II

## 15. REGULATORY INFORMATION

**TSCA Status:** (Toxic Substance Control Act Section 8(b) Inventory)

All chemical substances in this product are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

**SARA 313**

This product contains the following listed substances:

**Butoxyethanol**

CAS No 111-76-2 applies to R-(OCH<sub>2</sub>CH<sub>2</sub>)<sub>n</sub>-OR', where n = 1, 2, or 3, R=Alkyl C7 or less, or R = Phenyl or Alkyl substituted phenyl, R' = H or Alkyl C7 or less, or OR' consisting of Carboxylic acid ester, Sulfate, Phosphate, Nitrate, or Sulfonate  
Chemical Category N230

**SARA 311/312 Hazard Categories**

Acute Health Hazard:	Yes
Chronic Health Hazard:	Yes
Fire Hazard:	No
Sudden release of pressure hazard:	No
Reactive Hazard:	No

**California Proposition 65**

This product is not subject to warning requirements under California Proposition 65.

<b>16. OTHER INFORMATION</b>
------------------------------

<b>NFPA</b>	<b>Health Hazards: 3</b>	<b>Flammability: 0</b>	<b>Instability: 0</b>	<b>Special: N/A</b>
<b>HMIS</b>	<b>Health Hazards: 3</b>	<b>Flammability: 0</b>	<b>Physical Hazards: 0</b>	

**Revision Date:** 10-Apr-2020  
**Reasons for Revision:** Section, 2, 4, 10, 11, and, 14

**Disclaimer:**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**