

Safety Data Sheet Spartan Chemical Company, Inc.

Revision Date: 14-Oct-2019

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identifier Product Name: Product Number: Recommended Use: Uses Advised Against:	H2-D2 2485 Cleaning agent For Industrial and Institutional Use Only
Manufacturer/Supplier:	Spartan Chemical Company, Inc. 1110 Spartan Drive Maumee, Ohio 43537 USA 800-537-8990 (Business hours) www.spartanchemical.com
24 Hour Emergency Phone Numbers Medical Emergency/Information: Transportation/Spill/Leak:	s: 888-314-6171 CHEMTREC 800-424-9300
	2. HAZARDS IDENTIFICATION
GHS Classification Acute Toxicity - Oral: Skin Corrosion/Irritation: Serious Eye Damage/Eye Irritation: Corrosive to Metals:	Category 4 Category 1 Sub-category B Category 1 Category 1
<u>GHS Label Elements</u> Signal Word: Symbols:	Danger

Harmful if swallowed.

breathing.

May be corrosive to metals.

Do not breathe mist, vapors or spray.

present and easy to do. Continue rinsing.

Hazard Statements:

Precautionary Statements: Prevention:

Response: -Eyes

-Skin

-Inhalation:

-Ingestion:

Causes severe skin burns and serious eye damage.

Do not eat, drink or smoke when using this product

Keep in original or other corrosion resistant container.

or shower. Wash contaminated clothing before reuse.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

Wash hands and any exposed skin thoroughly after handling.

IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN.

Wear protective gloves. Wear eye / face protection. Wear protective clothing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water

-Specific Treatment:	See Safety Data Sheet Section 4: "FIRST AID MEASURES" for additional information.
Spill: Storage: Disposal:	Absorb spillage to prevent material damage. Store locked up. Store in corrosion resistant container. Dispose of contents and container in accordance with local, state and federal regulations.
Hazards Not Otherwise Classified:	Not Applicable
Other Information:	 Corrosive. Harmful contact may not cause immediate pain. Harmful if absorbed through skin. Inhalation of vapors or mist may cause respiratory irritation. Take off and destroy contaminated shoes.

- Keep out of reach of children.
- NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Water	7732-18-5	40-70
Butoxyethanol	111-76-2	10-30
Sodium Xylenesulfonate	1300-72-7	3-7
Tetrapotassium Pyrophosphate	7320-34-5	1-5
Potassium Hydroxide	1310-58-3	1-5
C9-11 Pareth-6	68439-46-3	1-5
Sodium Ethylhexyl Sulfate	126-92-1	1-5
Sodium Nitrite	7632-00-0	1-5
Acid Orange 7	633-96-5	<0.1

Specific chemical identity and/or exact percentage of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

-Eye Contact:	Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN.
-Skin Contact:	Take off immediately all contaminated clothing and shoes. Rinse with water or shower for at least 15 minutes. IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN. Wash contaminated clothing before reuse. Discard or destroy contaminated shoes.
-Inhalation:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN.
-Ingestion:	Rinse mouth. Do NOT induce vomiting. IMMEDIATELY CALL A POISON CENTER OR PHYSICIAN. Never give anything by mouth to an unconscious person.
Note to Physicians:	NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media:	Product does not support combustion, Use extinguishing agent suitable for type of surrounding fire
Specific Hazards Arising from the Chemical:	Dried product is capable of burning. Combustion products are toxic.
Hazardous Combustion Products:	May include Carbon monoxide Carbon dioxide and other toxic gases or vapors.
Protective Equipment and Precautions for Firefighters:	Wear MSHA/NIOSH approved self-contained breathing apparatus (SCBA) and full protective gear. Cool fire-exposed containers with water spray.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions: Environmental Precautions: Methods for Clean-Up:

Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. Do not rinse spill onto the ground, into storm sewers or bodies of water. Prevent further leakage or spillage if safe to do so. Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see Section 13).

7. HANDLING AND STORAGE

Advice	on	Safe	Handling:	
--------	----	------	-----------	--

Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly after handling. **Storage Conditions:** Keep containers tightly closed in a dry, cool and well-ventilated place. Keep out of the reach of children. Keep from freezing. **Incompatible Materials:** Incompatible with strong acids and bases. Incompatible with oxidizing agents.

Suggested Shelf Life:

Minimum of 2 years from date of manufacture.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Occupational Exposure Limits:

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH
Butoxyethanol 111-76-2	TWA: 20 ppm	TWA: 50 ppm TWA: 240 mg/m ³ (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m ³ (vacated) S* S*	IDLH: 700 ppm TWA: 5 ppm TWA: 24 mg/m ³
Potassium Hydroxide 1310-58-3	Ceiling: 2 mg/m ³	(vacated) Ceiling: 2 mg/m ³	Ceiling: 2 mg/m ³
Engineering Controls:	chemicals above the occupation engineering controls should be	t, fumes, gas, vapors or mists v onal exposure limits, local exha	ust ventilation or other
Personal Protective Equipment Eye/Face Protection:	Wear splash goggles. For seve	are use-conditions wear a face	shield over the goggles
Skin and Body Protection:	Wear splash goggles. For severe use-conditions, wear a face shield over the goggles. Wear rubber or other chemical-resistant gloves. Use of impervious apron, boots and other protective equipment should be considered in order to prevent or minimize contact with this product.		
Respiratory Protection:	Not required with expected use. If occupational exposure limits are exceeded or respiratory irritation occurs, use of a NIOSH/MSHA approved respirator suitable for the use-conditions and chemicals in Section 3 should be considered.		
General Hygiene Considerations:	Wash hands and any exposed skin thoroughly after handling. See 29 CFR 1910.132-138 for further guidance.		

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance/Physical State:	Liquid
Color:	Orange
Odor:	Mild
pH:	13.5-14.0
Melting Point / Freezing Point:	No information available.
Boiling Point / Boiling Range:	100 °C / 212 °F
Flash Point:	> 100 °C / > 212 °F ASTM D56
Evaporation Rate:	< 1 (Butyl acetate = 1)
Flammability (solid, gas)	No information available.
Upper Flammability Limit:	No information available.
Lower Flammability Limit:	No information available.
Vapor Pressure:	No information available.
Vapor Density:	No information available.
Specific Gravity:	1.07
Solubility(ies):	Soluble in water
Partition Coefficient:	No information available.
Autoignition Temperature:	No information available.
Decomposition Temperature:	No information available.
Viscosity:	No information available.

10. STABILITY AND REACTIVITY

Reactivity: Chemical Stability: Possibility of Hazardous Reactions: Conditions to Avoid: Incompatible Materials: Hazardous Decomposition Products:	This material is considered to be non-reactive under normal conditions of use. Stable under normal conditions. Contact with aluminum or other reactive metals may release hydrogen gas. Exposure to air or moisture over prolonged periods. Incompatible with strong acids and bases. Incompatible with oxidizing agents. Thermal decomposition can lead to release of irritating and toxic gases and vapors
	11. TOXICOLOGICAL INFORMATION
Likely Routes of Exposure: Symptoms of Exposure:	Eyes, Skin, Ingestion, Inhalation.
-Eye Contact:	Pain, redness, swelling of the conjunctiva and tissue damage. Eye contact may cause permanent damage.
-Skin Contact:	Pain, redness, blistering and possible chemical burn.
-Inhalation:	Irritation or damage to the mucus membranes of the respiratory tract. Nasal discomfort and coughing.
-Ingestion:	Damage or chemical burns to mouth, throat and stomach. Pain, nausea, vomiting and diarrhea.
Immediate, Delayed, Chronic Effects	S
Product Information:	Data not available or insufficient for classification.
Target Organ Effects:	Blood. Central nervous systemEyes. hematopoietic system. kidney. Liver. Respiratory SystemSkin.
Numerical Measures of Toxicity The following acute toxicity estimates	(ATE) are calculated based on the GHS document.
ATEmix (oral) [.]	1601 mg/kg

ATEmix (oral):	1601 mg/kg
ATEmix (dermal):	7338 mg/kg
ATEmix (inhalation-dust/mist):	9.8 mg/l

Component Acute Toxicity Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Water 7732-18-5	> 90 mL/kg (Rat)	Not Available	Not Available
Butoxyethanol 111-76-2	= 470 mg/kg (Rat)	= 99 mg/kg(Rabbit)	= 450 ppm (Rat)4 h

Sodium Xylenesulfonate 1300-72-7	= 1000 mg/kg(Rat)	Not Available	Not Available
Potassium Hydroxide 1310-58-3	= 284 mg/kg (Rat)	Not Available	Not Available
C9-11 Pareth-6 68439-46-3	= 1400 mg/kg(Rat)	Not Available	Not Available
Sodium Ethylhexyl Sulfate 126-92-1	= 4 g/kg (Rat)	Not Available	Not Available
Sodium Nitrite 7632-00-0	= 85 mg/kg (Rat)	Not Available	= 5.5 mg/L (Rat)4 h

Carcinogenicity: No components present at 0.1% or greater are listed as to being carcinogens by ACGIH, IARC, NTP or OSHA.

12. ECOLOGICAL INFORMATION

Chemical Name	Algae/Aquatic Plants	Fish	Toxicity to Microorganisms	Crustacea
Butoxyethanol 111-76-2	Not Available	1490: 96 h Lepomis macrochirus mg/L LC50 static 2950: 96 h Lepomis macrochirus mg/L LC50	Not Available	1000: 48 h Daphnia magna mg/L EC50
Tetrapotassium Pyrophosphate 7320-34-5	Not Available	100: 96 h Oncorhynchus mykiss mg/L LC50	Not Available	100: 48 h water flea mg/L EC50
Sodium Nitrite 7632-00-0	Not Available	0.19: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 0.092 - 0.13: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 0.4 - 0.6: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 0.65 - 1: 96 h Oncorhynchus mykiss mg/L LC50 static 2.3: 96 h Pimephales promelas mg/L LC50 flow-through 20: 96 h Pimephales promelas mg/L LC50 static	Not Available	Not Available

Persistence and Degradability:	No information available.
Bioaccumulation:	No information available.
Other Adverse Effects:	No information available.

13. DISPOSAL CONSIDERATIONS

Disposal of Wastes:	This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).
Contaminated Packaging:	Do not reuse container.
US EPA Waste Number:	D002

14. TRANSPORT INFORMATION

UN1760 Corrosive liquids, n.o.s., (contains potassium hydroxide) 8 II
For totes add: RQ, I.B.C.

Special Provisions:	Shipping descriptions may vary based on mode of transport, quantities, package size, and/or origin and destination. Check with a trained hazardous materials transportation expert for information specific to your situation.	
IMDG:		
UN/ID No:	UN1760	
Proper Shipping Name:	Corrosive liquids, n.o.s., (contains potassium hydroxide)	
Hazard Class:	8	
Packing Group:		
Reportable Quantity (RQ):	For totes add: RQ, I.B.C.	

15. REGULATORY INFORMATION

TSCA Status: (Toxic Substance Control Act Section 8(b) Inventory)

All chemical substances in this product are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

SARA 313

This product contains the following listed substances:

Butoxyethanol

CAS No 111-76-2 applies to R-(OCH2CH2)n-OR', where n = 1, 2, or 3, R=Alkyl C7 or less, or R = Phenyl or Alkyl substituted phenyl, R' = H or Alkyl C7 or less, or OR' consisting of Carboxylic acid ester, Sulfate, Phosphate, Nitrate, or SulfonateChemical Category N230

Sodium Nitrite CAS No 7632-00-0

SARA 311/312 Hazard Categories	
Acute Health Hazard:	Yes
Chronic Health Hazard:	Yes
Fire Hazard:	No
Sudden release of pressure hazard:	No
Reactive Hazard:	No

California Proposition 65

This product is not subject to warning requirements under California Proposition 65.

16. OTHER INFORMATION

NFPA	Health Hazards: 3	Flammability: 0	Instability: 0	Special: N/A
HMIS	Health Hazards: 3*	Flammability: 0	Physical Hazards: 0	
Revision Date: Reasons for Revision:	14-Oct-2019 Revised formula			

Disclaimer:

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet